

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: +49 - (0)81 41 - 52 71-0

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. +49 - (0)81 41 - 52 71-0 E-
Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

DATA SHEET ABOUT

SmartModuleS

Touch Display Device



ITEM NUMBER: 163417

The basic configuration of the SmartModuleS includes an industrial-grade mini PC with integrated UPS built into a robust aluminum housing. It also comes with GBIT LAN, WLAN, Bluetooth, USB 3.0 and DP interfaces. This provides a “self-sufficient” test environment and complete test sequences can be developed directly on the device. It also includes a touch display for direct operation without additional devices. The specially designed graphical user interfaces of the MCD Toolmonitors make the device easy to use.

- // Dimensions: 425 x 270 x 133 (LWH)
- // 24 V / 300 W external power supply
- // 8 GB LPDDR RAM, 64 GB eMMC flash memory, Windows 11 IoT
- // Color RAL7016 (anthracite grey), other colors at extra charge
- // 4x module slots (7 HP each)
- // 1x display port for additional monitor or if no display module is installed
- // 2x LAN RJ45 Gigabit 100 MB / 10 MB
- // 2x USB Port 3.1 type A, 1x USB port 3.1 type C (with PD and DP alternative mode)
- // 7" LCD Display, 1280 x 800 pixels resolution, 320 cd / m² luminance, capacitive touch

